



STEP INTO STYLE

INTENSE

# INTENSE

Intense is an expression of the depth of the power of endurance that is the essence of this category. These 20 mm high performance tiles, with special anti - skid properties, are created to withstand the elements over time, to bring you a synthesis of durability and style across outdoor applications : gardens, swimming pools, outdoor decks, verandahs and more.

## CONSTONE COLLECTION

A part of the Intense Category, Constone Collection reflects a synergy of attributes drawn from the natural aesthetics of stone and the legendary robustness of concrete.

These are 20mm tiles, created specially for those spaces where design concepts need to converge beauty with intrinsic strength to withstand the rigours of versatile functionality.

This in its turn enables seamless flow of the aesthetic boundaries between interior and exterior flooring reflects a synergy of attributes drawn from the natural aesthetics of stone and concrete.

# Constone Collection

1

## Design

Constone reflects contemporary elegance while adding natural accents to outdoor spaces

4

## Inspirations

2 Cold looks and 2 Warm looks inspired by the primal perfection of stone and the strength of concrete

3

## Sizes

To ensure all the potential of design versatility.

- 20 mm thickness tile



- Anti Skid Surface - R 11



- Load Bearing







# Constone Collection - 20 mm (Cold)

Verde



Available sizes:	No. of faces
60 x 60 cm	40
30 x 60 cm	80
30 x 30 cm	160

Grigio



Available sizes:	No. of faces
60 x 60 cm	40
30 x 60 cm	80
30 x 30 cm	160

# Constone Collection - 20 mm (Warm)

Crema



Available sizes:	No. of faces
60 x 60 cm	40
30 x 60 cm	80
30 x 30 cm	160

Rust



Available sizes:	No. of faces
60 x 60 cm	40
30 x 60 cm	80
30 x 30 cm	160



# Constone Collection - Faces

CONSTONE RUST

SIZE 600X600



# Modular Laying

CONSTONE VERDE



60 x 60	37.00 %
30 x 60	35.57 %
30 x 30	27.43 %

CONSTONE GRIGIO



60 x 60	37.00 %
30 x 60	35.57 %
30 x 30	27.43 %



# Modular Laying

CONSTONE CREMA



60 x 60	37.00 %
30 x 60	35.57 %
30 x 30	27.43 %

CONSTONE RUST



60 x 60	37.00 %
30 x 60	35.57 %
30 x 30	27.43 %

# Applications



Adhesive



Grass



Gravel



Sand



Raised Floor

# Cut Pc Box





# Actual Box Packing



ISPIRA QUALITY STANDARDS				
Standards according to ISO 13006: Annex G - EN 14411: Annex G. Dry - Pressed Ceramic Tiles.				
TECHNICAL FEATURES	STANDARD METHOD ISO	UNIT	REQUIREMENTS ISO 13006:2018(E) $E_v \leq 0.5\%$ GROUP BIa	ISPIRA VALUES
MOHS HARDNESS OF SURFACE	ASTM C 1895-20	-	-	7
BREAKING STRENGTH	ISO 10545-4		Not less than 1300 N	Min. 10000 N
SURFACE ABRASION	ISO 10545 - 7	-	Report abrasion class and cycles passed	CLASS 4 (6000 cycles)
SLIP RESISTANCE DCOF/R-Class	ANSI A137.1	-	DCOF > 0.42	DCOF > 0.65
	DIN 51130	-	Min. R-9	R-11
STAIN RESISTANCE	ISO 10545 - 14	Class	Minimum Class 3	CLASS 3
CHEMICAL RESISTANCE	ISO 10545 - 13	Class	Minimum B	Compliant

# Domestic Packing Details

Nominal Size	Thickness mm	Pcs. x box	Sq. mtr x box	Sq. ft x box	Weight x box (kg)
60 x 60	20	2	0.71	7.64	33
30 x 60	20	4	0.71	7.64	33
30 x 30	20	4	0.35	3.77	16

## Actual Size

Standard Size cm	Actual Size cm
60 x 60	59.6 x 59.6
30 x 60	29.6 x 59.6
30 x 30	29.6 x 29.6

\* We recommend to use 4mm spacer for all sizes.



Thank You